

Doc. No.: SDS - AL007B Page: Page 1 of 6

Owner: SHEQ

Rev. Date: September, 2022

# Nitrogen (Liquid)

# NITROGEN (Refrigerated)





### 1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : Nitrogen (Liquid)

MSDS No. : AL007B
Chemical Formula : N2

Company Identification : Air Liquide Egypt

Main Office : Polyom Building - 2nd floor

Area 22 - 1st Sector- Road 90 (Downtown)-5th Settlement-

11835 New Cairo-Cairo

Phone No. : +20 2 23221100 FAX : +20 2 25213100

#### **2 HAZARDS IDENTIFICATION**

### Classification of the substance

Physical Hazard : Gases under pressure - Refrigerated liquefied gas

Health Hazard : no acute toxicity

#### **Label Elements**

Hazard Pictogram



• Signal word : Warning



SDS - AL007B Doc. No.: Page: Page 2 of 6

Owner: SHEQ

Rev. Date: September, 2022

# Nitrogen (Liquid)

### 2 HAZARDS IDENTIFICATION (continued)

**Hazard Statement** : Contains refrigerated gas; may cause cryogenic burns or

injury

**Precautionary statements** 

Prevention : Wear cold insulating gloves / face shield / eye protection Response

: Thaw frosted parts with lukewarm water. Do not rub affected

: Get immediate medical advice / attention

Storage : Store in a well ventilated area

Other Hazard

Other hazards : Contact with product may cause cold burns or frostbite.

In high concentration may cause asphyxiation.

#### **3 COMPOSITION / INFORMATION ON INGREDIENTS**

**Substance / Preparation** : Substance

Substance Name Contents CAS No. EC No. Index No. Classification

Nitrogen (refrigerated) 100% 7727-37-9 231-783-9

Contains no other components or impurities which will influence the classification of the product.

#### **4 FIRST AID MEASURES**

**First Aid Measures** 

- Inhalation : In high concentrations may cause asphyxiation. Symptoms may include loss

of mobility / consciousness. Victim may not be aware of asphyxiation

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial

respiration if breathing stopped.

- Skin / Eye Contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

In case of frostbite spray with water for at least 15 minutes. Apply a sterile

dressing. Obtain medical assistance.

: Ingestion is not considered a potential route of exposure. - Ingestion



Doc. No.: SDS - AL007B Page: Page 3 of 6

Owner:

Rev. Date: September, 2022

SHEQ

Nitrogen (Liquid)

#### **5 FIRE FIGHTING MEASURES**

Flammable class : Non flammable

Specific hazards : Exposure to fire may cause containers to rupture / explode

Hazardous Combustion Products : None

**Extinguishing media** 

- Suitable extinguishing media : All known extinguishants can be used.

**Specific methods** : If possible stop flow of product.

Move away from the container and cool with water from a protected position. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain

fire.

Special protective equipment for

fire fighters

: In confined space use self-contained breathing

apparatus

#### **6 ACCIDENTAL RELEASE MEASURES**

Personal precautions : Evacuate area

Use protective clothing

Wear self-contained breathing apparatus when entering area

unless atmosphere is proved to be safe.

Ensure adequate air ventilation.

**Environmental Precautions** : Try to stop release.

Prevent from entering sewers, basements and workpits, or any

place where its accumulation can be dangerous.

Clean up methods : Ventilate area.

### **7 HANDLING AND STORAGE**

**Storage** : Keep container below 50 degrees C in a well ventilated place.

**Handling** : Suck back of water into the container must be prevented

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas

supplier if in doubt.

Refer to supplier's container handling instructions.



Doc. No.: SDS - AL007B Page: Page 4 of 6

Owner: SHEQ

Rev. Date: September, 2022

# Nitrogen (Liquid)

#### **8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection**: Ensure adequate ventilation.

Protect eyes, face and skin from liquid splashes.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 degrees C : Refrigerated liquefied gas.

Color : Colorless liquid

Odor : No odor warning properties

Molecular Weight : 28

Melting point (degrees C) : -210

Boiling point (degrees C) : -196

Critical temperature (degrees C) : -147

Vapor pressure, 20 degrees C : Not Applicable

Relative density, gas (air =1) : 0.97

Relative density, liquid (water = 1) : 0.8

Solubility in water [mg/l] : 20

Other data : Gas/vapor heavier than air. May accumulate in confined

spaces, particularly at or below ground level.

#### 10 STABILITY AND REACTIVITY

**Stability and reactivity** : Stable under normal conditions.

Liquid spillages can cause embrittlement of structural

materials.



Doc. No.: SDS - AL007B Page: Page 5 of 6

Owner: SHEQ

Rev. Date: September, 2022

# Nitrogen (Liquid)

### 11 TOXICOLOGICAL INFORMATION

**Toxicity information** : No known toxicological effects from this product

### 12 ECOLOGICAL INFORMATION

**Ecological effects information** : Can cause frost damage to vegetation.

#### 13 DISPOSAL CONSIDERATIONS

General : Do not discharge into any place where its accumulation could

be dangerous.

Contact supplier if guidance is required.

#### 14 TRANSPORT INFORMATION

UN No. : 1977 H.I. nr : 22 ADR / RID

- Proper shipping name : Nitrogen, Refrigerated Liquid - ADR Class

- ADR / RID Classification code :3A - Labelling ADR



2.2: Non flammable, non toxic gas.

### Other transport information

: Avoid transport on vehicles where the load space is not separated from the driver's compartment

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.



Doc. No.: SDS - AL007B
Page: Page 6 of 6

Owner: SHEQ

Rev. Date: September, 2022

# Nitrogen (Liquid)

### 14 TRANSPORT INFORMATION (continued)

- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations

#### 15 REGULATORY INFORMATION

**EC Classification** : Not included in Annex I.

Not classified as dangerous preparation / substance

**EC Labeling** : No EC labeling required.

- Symbol (s) : None
- R Phrase (s) : None
- S Phrase (s) : None

#### **16 OTHER INFORMATION**

- May cause frostbite.
- Keep container in a well-ventilated place.
- Do not breathe the gas.
- Ensure all national / local regulations are observed.
- Asphyxiant in high concentrations.
- The hazard of asphyxiation is often overlooked and must be stressed during operator training.
- This Material Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.
- Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
- Details given in this document are believed to be correct at the time of going to press. Whilst proper care
  has been taken in the preparation of this document, no liability for injury or damage resulting from its use
  can be accepted.

#### Recommended uses and restrictions:

This MSDS is for information purposes only and is subject to change without prior notice. [Prior to purchase of products, please contact your local AIR LIQUIDE office for complete MSDS (with Manufacturer's name and emergency phone number)].

**End of Document**